



Energy  
Jobs  
Network

30-day Free Promotion

The Electricity Forum website has partnered with Energy Jobs Network (EJN) to be your one stop shop for all of your staffing needs.

Visit:

[www.electricityforum.com](http://www.electricityforum.com)

ISSUE 9, 2001

# *HV Engineering, Operations, Construction & Maintenance* **ELECTRICITY** *Power Generation, Transmission & Distribution, Utilization* **TODAY**



## Paths to Interconnection Protection

Wye ungrounded-Delta

Delta-Delta

Delta-Wye grounded

Wye-Wye grounded

Wye grounded-Delta

### PROTECTION AND CONTROL

Relaying for Dual Supply Lines

• IPP Protection:

Interconnection Transformer Winding Arrangement Implications

### ELECTRICITY RESTRUCTURING

Report on Restructuring of the Canadian Electricity Industry

• Observations on Electricity Trends and Issues

### POWER QUALITY

Power Quality Q&A

### GENERATION

Creating Potential Revenue Gains from Hydro Turbines Using Computational Fluid Dynamics Simulations

# CONNECTING... PROTECTING



## YOUR COMPETITIVE ADVANTAGE

We have the products and know-how you need for planning, constructing and maintaining your distribution and transmission networks. No manufacturer has the breadth of distribution products like Hubbell. From simple hardware and tools to sophisticated switching, protection, cable and insulation systems, Hubbell helps you cut costs, save time and increase efficiency.

For transmission and distribution, go no further than Hubbell. We have the products, support and expertise to *ensure your competitive advantage.*





**Publisher/Executive Editor**  
Randolph W. Hurst  
rwh@istar.ca

**Managing Editor/  
Production Manager**  
Kelly Jones-Johnston  
kjj@electricityforum.com

**Production Coordinator**  
Chantelle Simpson  
chantelle@electricityforum.com

**Advertising Sales**  
Donna Gilliland  
donna@electricityforum.com  
Carol Gardner  
carol@electricityforum.com

**Web Site Advertising Sales**  
Barbara John  
forum@capital.net

**Circulation Manager**  
Colleen Flaherty  
colleen@electricityforum.com

**Visit our Web Site:**  
www.electricityforum.com  
**E-mail:** hq@electricityforum.com

Electricity Today is published 10 times a year by The Canadian Electricity Forum. The Canadian Electricity Forum is the conference management and publishing company for Canada's electric power and engineering industry and is a division of The Hurst Communications Group Inc.

Electricity Today is distributed free of charge to Canadian electric utility personnel involved in management, engineering and operations; plant management, electrical engineering and electrical maintenance personnel within major Canadian power consuming industries; and electrical engineering consultants.

Paid subscriptions are available to all others: in Canada - \$40.00 per year (10 issues)(GST extra); in the U.S. - \$50.00 per year (\$US); international - \$100.00 (\$US) per year. All requests for free subscriptions or changes to free subscriptions (i.e. address changes) must be made in writing. All correspondence should be directed to: Subscription Manager, Electricity Today, Suite 101, 345 Kingston Road, Pickering, Ontario, L1V 1A1

Canada Post - Canadian Publications Mail  
Product Sales Agreement 104876  
ISSN 0843-7343

Printed in Canada. All rights reserved.

The contents of this publication may not be reproduced in whole or in part without prior permission from the publisher  
Member of:



# IN THIS ISSUE

## PROTECTION AND CONTROL

Relaying for Dual Supply Lines .....	5
IPP Protection: Interconnection Transformer Winding Arrangement Implications .....	14

## ELECTRICITY RESTRUCTURING

Report on Restructuring of the Canadian Electricity Industry .....	6
Observations on Electricity Trends and Issues .....	9

## POWER QUALITY

Power Quality Q&A .....	18
-------------------------	----

## GENERATION

Creating Potential Revenue Gains from Hydro Turbines Using Computational Fluid Dynamics Simulations .....	20
---	----

## PRODUCT AND SERVICE SHOWCASE FOCUS

A Showcase of Products and Services .....	28, 29
---	--------

## ADVERTISER INFORMATION

Advertisers' Index and Reader Inquiry Information .....	30
---	----





## Catch Every Surge.

**There's a Brews/Horstmann faulted circuit indicator capable of handling anything that human error, system failure or mother nature can dish out.**

One size fits all, our Navigator faulted circuit indicators are easily installed or removed on bare overhead conductor. Featuring new super bright LEDs, they are highly visible, guiding trouble crews in a hurry to restore power or trying to source troublesome temporary faults.

Get the ultimate protection from downtime and damage.

Brews/Horstmann faulted circuit indicators: lighting the way.



**Count on Horstmann Brews Power Play Team to power your profits.**



**UTILITY SALES  
DIVISION  
THE POWER  
CONNECTION**



Brews are nationally recognized utilities experts. Brews' Specialist **Don**

**Henderson** is thoroughly familiar with the Horstmann product and its potential to ensure greater efficiency and increased profits.

**R.L. Brews Ltd.**

10810 - 119 Street,  
Edmonton, Alberta T5H 3P2  
Phone: (780) 452-3730 Fax: (780) 455-4422

**Toll Free Customer Service: 1-800-661-3730**  
**Visit our Website at [www.rlbrews.com](http://www.rlbrews.com)**



# Relaying for Dual Supply Lines

By Paul Kruger

The importance of a reliable supply of electricity for many manufacturing and heavy industrial process plants cannot be overemphasized. Momentary interruptions and even temporary voltage sags or spikes can have as detrimental an impact as long term interruptions. Such events can wreak havoc with manufacturing processes and the sensitive solid state equipment that is now routinely used to control them.

One solution to the problem is to install dual supply lines. However, depending upon plant location and distribution system configuration, a second supply line could cost millions of dollars. For some heavy power users, even this level of investment can often be justified. But what if a company were to make such an investment, only to discover that serious supply problems continue to plague them? Having two supply lines does not always improve the reliability of the power supply for important loads.

Such was the case at an industrial plant in Eastern Ontario.

The plant has a typical two line 115KV supply with two transformers, low side transformer breakers and a normally closed bus tie breaker. The low voltage busses operate at 4200 volts. The low side bus tie potentially offers an uninterrupted supply to the load, but it also introduces the possibility that a fault on one line may affect the second, and the prospect of backfeed through the tie if the transformer breaker fails to clear on a line fault.

Such installations are normally protected by directional over current relays, over/under voltage relays, pilot wire, remote (transfer) trip from the distribution utility, or some combination thereof. Directional over current relays are generally timed and therefore slow. Pilot wire is fast but prone to false operations. Unfortunately, both remote trip and pilot wire require either expensive relaying to

enable wireless communication between the terminals, or land lines which can also be expensive. Furthermore, remote tripping is relatively slow, with a time to trip initiation in the range of 40 to 50 ms, and is prone to both false tripping and failure to trip.

The plant in question originally had timed directional over current protection, timed under/over voltage protection, and remote tripping from the local utility, but

line, through the low voltage bus tie. The voltage dip at the plant was always so severe that the process control would shut the plant down and / or the large compressor motors would fall out of synchronism and trip off.

In essence, the manufacturer had paid for a Cadillac two supply line system, and as a result had doubled its exposure to line faults because a failure on either supply line would shut down the manufacturing process.



The problem, then, was to find a cost effective local substitute for remote trip or pilot wire protection, one that would clear faults reliably and with sufficient speed to prevent the process control from being affected by the momentary voltage sags that accompanied every electrical fault on either of the supply lines. The solution was surprisingly simple.

Two sets of specialized directional over current relays were installed. Each set was supplied from both sets of transformer breaker current transformers, connected in a differential configuration. This arrangement permits much greater fault discrimination as it results in little or no relay current during normal conditions, but the relay current doubles when fault or load current backfeeds through the low tension bus.

One of the protections utilizes two directional overcurrent relays type KCEG from GEC Alsthom, each directioned for current flow out of one of the 115 KV lines. The setting for the relay is 1000 amps flowing back through the transformer breakers, and it operates on current in any phase. It is supervised by pallet switches from the other breaker and by bus under voltage, set at 3500 volts. Thus configured, the KCEG relays will operate for any line fault on their associated line, or on a backfeed to connected remote loads after a fault clearance at the supply station.

During the past 5 years, the KCEG

**Continued on page 29**



the remote tripping proved to be so prone to false operations that it was abandoned. Most, but not all, of the other load terminals on the two lines had transfer tripping.

Consequently, every time either of the two lines was affected by lightning or any other fault, the terminals with transfer tripping cleared and left the plant hanging on to the faulted line, until the directional relays finally timed out. During this time the plant would carry the remaining load left on the faulted

## ELECTRICITY RESTRUCTURING

# Report on Restructuring of the Canadian Electricity Industry

In the traditional market structure of the electricity industry, generation, transmission and distribution of electricity are owned and managed by vertically-integrated monopolies. This form of market structure, which still prevails in much of Canada today, was widely adopted because the electricity supply industry was regarded as a natural monopoly. With respect to generation, this meant that lowest costs could be achieved by building large scale power plants. The nature of long-distance transmission systems and local distribution systems also fit the natural monopoly model. Even if competition were possible in generation, it would still not be economically feasible to build competing transmission and distribution facilities to serve the same market, i.e., lowest costs would be achieved by one facility.

Because of the concern that monopolies would be able to exercise market power, their operations were either overseen by regulatory bodies acting in the public interest or, in the case of most Canadian provinces, public ownership was established in the form of Crown corporations.

The utilities in each province tended to develop their own generation, transmission and distribution systems consistent with provincial energy requirements. In addition, interprovincial and international transmission ties were made to achieve anticipated benefits such as:

- cost savings due to lower installed reserve requirements;
- the ability to install larger, more economical generating units;
- seasonal diversity and economy energy exchanges;
- the ability to enter into firm power contracts; and
- other anticipated benefits such as service reliability and emergency assistance.

In Canada and the U.S., a number of trends began to emerge in the late 1980s and early 1990s that caused several jurisdictions to question the traditional market structure:

- (i) Technological advances in generation made the construction of smaller gas-fired generating units feasible, particularly combined-cycle natural gas turbines. These units can provide incremental supply at lower capital costs, and can be built more quickly than conventional fossil fuel or nuclear plants. At the same time, it was profitable for industrial electricity consumers to purchase natural gas to simultaneously produce process heat and electricity (cogeneration) and to sell any surplus electricity into the electricity grid.
- (ii) Many jurisdictions, for example in the U.S. Northeast and California, took the view that access to a utility's transmission lines should be made available to other service providers to provide access to cheaper supplies from neighbouring regions, and regions further afield. This would require obtaining non-discriminatory access to transmission systems.
- (iii) Experience with deregulation and restructuring in other industries such as telecommunications, natural gas and the airlines suggested that competition between producers and service providers would lower costs and provide a broader selection of services to consumers.

## Restructuring Defined

Restructuring refers to reorganizing electric utilities from vertically-integrated monopolies into separate generation, transmission and distribution service companies. This separation, or unbundling, is intended to promote competition between generators, and to "open" the transmission and distribution systems, eventually increasing competition in the supply and marketing of electricity. Increased competition offers more choices to consumers such as choice of supplier, expanded metering services and options with respect to 'green power.'

Two essential aspects of restructuring are wholesale access and retail access. Wholesale access refers to generators having the ability to obtain access to transmission systems to


**GO  
ZENSOL.COM  
AND CLICK  
INTO YOUR  
WORLD**

YOUR WORLD IS OUR WORLD TOO. WE HAD A WISH. We wanted to make a special contribution—something thorough. We did. We put down on paper this great big World of High Voltage Circuit Breaker Testing, in an extensive technical article on our website. Now we have another wish, we would like to know what you think. **GO TO ZENSOL.COM, CLICK TIMING & MOTION, AND PLEASE GET BACK TO US.**

**ZENSOL.COM**  
ZENSOL AUTOMATION INC.

Timing & Motion

2.1.1 Arcing  
2.1.1.1 Insertion re-  
2.1.1.2 Operating re-  
2.1.2 Control  
2.1.3 Functioning  
2.2 Reliability  
2.2.1 Correct function  
2.2.2 Correlation cycles  
2.2.3 Circuit breaker types  
2.3 Interrupting medium  
2.3.1 Mineral oil  
2.3.2 Compressed air  
2.3.3 Sulfur hexafluoride  
2.3.4 Air blast  
3. CIRCUIT BREAKER  
3.1 Definition  
3.2 Importance  
3.3 Connection  
3.4



Canadian Electricity Demand

compete in for wholesale markets, which may include distribution companies or independent marketers. Retail access refers to marketers having the ability to obtain access to distribution systems to sell to end-use consumers, and conversely, allowing end-use consumers a choice among marketers. Full retail access occurs when all end-use consumers have this choice. Wholesale access can occur without retail access; however, retail access requires wholesale access.

### Restructuring Initiatives

In Canada, the movement toward restructuring the electricity industry has been uneven, as each province assesses its own unique regional circumstances and issues. Alberta restructured its electricity market over a five-year period culminating in full retail access on January 1, 2001. Ontario plans to implement full retail access in May 2002.

Most other provinces, including New Brunswick, Québec, Manitoba, Saskatchewan, and B. C. have implemented, or are planning to implement, wholesale access. Aside from Ontario and Alberta, no other provinces are planning to implement full retail access.

In the U.S., competition in generation was introduced when the Public Utilities Regulatory Policy Act was passed in 1979. This allowed, under various restrictions, independent power producers to sell into wholesale markets, thus ending utility monopoly over generation. Significant legislation emerged in the Energy Policy Act of 1992. This act mandated the U.S. Federal Regulatory Commission (FERC) to implement open access to transmission systems and eventually resulted in FERC Order 888 (1996). The order requires that "transmission customers of jurisdictional utilities who take service under the open access tariff and who own, control, or operate transmission facilities must, in turn, provide open access service to the transmitting utility." Order 888 has implications for Canadian electricity exporters. It effectively requires that Canadian transmission companies provide U.S. marketers access to their transmission facilities so that Canadian exporters utilizing those facilities, and open access systems in the U.S., may obtain a licence from FERC to market electricity in U.S. wholesale markets. This is referred to as the reciprocity requirement of Order 888.

Most recently, to further facilitate competitive wholesale markets, FERC Order 2000 (December 1999) required transmission companies under FERC jurisdiction to form Regional Transmission Organizations (RTOs) by December 2001, and defined the characteristics and functions that qualify an RTO. In view of the interconnections between U.S. and Canadian transmission systems, FERC encouraged Canadian participa-

tion. In Canada, the tariffs of electricity transmission systems are in the purview of the provinces. Thus the NEB does not have FERC-like jurisdiction.

While FERC regulates interstate transmission and has a mandate to ensure that consumers have access to electricity at fair and reasonable rates, retail access is largely the responsibility of individual states. As of mid-2000, approximately 21 percent of U.S. electricity customers had retail access; however, less than one percent, accounting for 1.5 percent of load, have exercised the option. The reason for the low participation is that, to date, the new marketers have not been able to compete successfully with the incumbent utilities.

In addition to the initiatives undertaken in Canada and the U.S., restructuring of the electricity industry has been underway in several other countries during the past decade. In Australia, New Zealand and the United Kingdom this required the unbundling of government-owned monopolies.


### RESTRUCTURING ISSUES

#### Stranded Costs and Benefits

An initial concern regarding the restructuring of electricity markets was that some generating plants would not be economic in a competitive environment and that they would become 'stranded' from the system. Consequently, their market value would be below book value, resulting in potentially large losses for the utilities owning these plants. The issue arose as to how these costs would be recovered.

In Ontario, the outstanding debt from Ontario Hydro has been referred to as a stranded cost. The debt is being managed

**Continued on page 9**



MINIATURE

## Frequency Meters With LED Displays



Free catalog


- 60Hz @ 120/220Vac or 400Hz @ 120Vac
- Two simple connections; No external power
- $\pm 0.1$ Hz accuracy; 1.38" x 0.88" packages
- Rugged epoxy-encapsulated construction

**DATEL**

For Frequency Meter data sheets  
[www.datel.com/ac5.htm](http://www.datel.com/ac5.htm)

DATEL, Inc., 11 Cabot Blvd., Mansfield, MA 02048  
Tel: 508-339-3000 800-233-2765  
E-mail: [sales@datel.com](mailto:sales@datel.com) ISO-9001 Registered

# GET CONNECTED!




At the Intertie, Even Small Independent Power Producers Require Utility-Grade Protection To Guard Against Islanding.

## Optimize Utility IPP Interconnection Protection with Metering, Waveform Capture, and Communications

### Reduce Project Costs:

- Standardization for most powerpool and utility interconnection requirements
- Commissioning tools to speed FAT and field start-up
- Forensic engineering capabilities for warranty investigations
- Programmable I/O and elements to meet different trip assignment requirements

The M-3410 Intertie/Generator Protection Relay provides loss of supply protection, as well as additional protective elements, metering, logging and communications, to provide a comprehensive intertie system.



*Get Connected with*

**BECKWITH  
ELECTRIC**  **CO. INC.**

6190 - 118th Avenue North, Largo, FL 33773-3724 USA  
 PHONE 727- 544-2326  
 FAX 727- 546- 0121  
 WEB [www.beckwithelectric.com](http://www.beckwithelectric.com)  
 E-MAIL [marketing@beckwithelectric.com](mailto:marketing@beckwithelectric.com)



**continued from page 7**

by a successor company to Ontario Hydro and will be recovered from Ontario electricity customers based on consumption.

In the U.S., stranded costs were associated with some nuclear facilities and older, less-efficient fossil fuel plants. Various ways have been designed to recover stranded costs, such as securitization and direct recovery through transition charges on electricity transmission and distribution.

Overall, as events have unfolded in the U.S., stranded costs have not been an impediment to restructuring. Initially, many utilities expected they would face burdensome stranded debt that they might not be able to recover, either because of market conditions or because some states would not allow these costs to be passed on to consumers. In fact, state regulators have allowed for full recovery and, because prices in bulk power markets have been stronger than anticipated, prices have tended to support higher values for these assets.

Stranded benefits can occur when the market value of divested assets is greater than the book value. In Alberta's restructuring scheme, a stranded benefit was associated with older generating plants. The value was established at auctions that sold the rights to market the power from these plants. The residual value between the prices bid for the power and the cost of operating the plants is being returned to Alberta consumers in the form of deductions from their monthly electricity bills.

**Market Power**

When considering restructuring for their respective jurisdictions, regulators have been concerned that market power might be exercised in some segments of the electricity market. For example, generators that own substantial amounts of capacity (province-wide or at strategic locations) could be in a position to prevent competing suppliers from entering a particular marketplace. Transmission facility owners might be able to withhold transmission access from competitive generators. In a restructured environment, incumbent distribution utilities may be in a position to take greater advantage of new market opportunities than their competitors because they have better access to customer information.

Ontario and Alberta have each taken steps to mitigate market power. In Ontario, the Market Power Mitigation

**continued on page 10**

## Observations on Canadian Electricity Trends and Issues

The electric power industry in North America has been undergoing substantial change as many jurisdictions have introduced competition in generation and provide access to wholesale markets and some retail markets. However, the pace of restructuring varies across regions and the extent to which restructuring will occur is uncertain. A key concern is the impact on electricity prices. Volatile oil and especially natural gas prices during the past two years have also been cause for uncertainty about electricity prices, because of the increasing use of gas in power generation. Given these concerns, this report has provided a detailed analysis of Canadian electricity markets, which has led to the following observations.

**Electricity Supply**

Overall, Canadian electricity markets appear to be adequately supplied. Alberta has experienced relatively tight supply situations, particularly during periods of peak demand. However, recent announcements suggest that power developers are planning to make new supplies available over the next one to five years.

Across the country, with a few notable exceptions, new generation projects in the near term are expected to be gas-fired. These plans were, for the most part, made before the recent escalation in natural gas prices. Depending on the duration of higher gas prices, there could well be a shift toward other forms of electricity generation. In recent months, there have been announcements of new coal-fired generation projects in Alberta, which has abundant and inexpensive coal. Higher prices tend to make wind energy and other renewable technologies more feasible.

The nature of gas-fired generation plants allows them to be built closer to load centres. Although not a focus of this report, this could be an important consideration in provinces where the current coal and hydroelectric generation facilities are located far from markets, thus requiring the construction of transmission capacity (e.g., Alberta, Saskatchewan, Manitoba and Québec). A related matter is future

trends in distributed generation; locating generation at industrial sites, for example, could reduce the need for both long-distance transmission and distribution facilities.

**Convergence**

Convergence of the natural gas and electricity markets is an outcome of the increasing use of gas in power generation. An important aspect is that gas prices and power prices have become closely related. Convergence is demonstrated by some recent trends: high natural gas prices throughout the U.S. affecting overall Canadian electricity export revenues; the price of natural gas influencing electricity prices in the Power Pool of Alberta; and electricity demand in California contributing to relatively high prices for B.C. gas exports.

**The Role of Electricity Exports and Market Integration**

A number of provinces have surplus energy available for export, and the country continues to be a net exporter of electricity. Exports comprised about nine percent of domestic generation in 2000.

Some Canadian entities have been granted wholesale trader status by FERC by satisfying the reciprocity requirements of open access under FERC Order 888. To further facilitate Canadian exporters' access to U.S. markets, and to facilitate access to U.S. supplies by Canadians, the transmission companies in several provinces are considering membership in RTOs. By consolidating the operations of a number of transmission systems into one independent entity, which would establish a standard tariff, RTOs further the objective of opening access to transmission. Canadian entities are not subject to FERC regulation, but due to the integrated nature of the North American transmission system, it appears that Canadian involvement in RTO formation could be potentially beneficial to all market participants, provided proper approaches for jointly overseeing a cross-border RTO are adopted.

Directionally, the formation of

**continued on page 12**

### Continued from page 9


Agreement established Ontario Power Generation's licence conditions and an Independent Market Operator has been established to assure non-discriminatory access to transmission.

Alberta's ap-proach to mitigate market power includes the creation of an independent power pool and an independent transmission administrator, as well as the auctions of power plant output to reduce the market share of incumbent generators.

### Reliability

Traditionally, electric generating utilities operated with high reserve margins, often in the range of 20 to 25 percent above peak demand. This was deemed necessary and prudent because of potential unscheduled plant outages. In restructured markets operating margins tend to be lower; therefore, other things being equal, the prospects of supply disruptions are greater, although costs are lower.

With the unbundling of the generation, transmission and distribution functions, reliability becomes more of a shared responsibility between these enti-



Interprovincial Transfers of Electricity

ties and is reflected in their tariff provisions (terms of service).

### Marginal Cost versus Average Cost Pricing

In the traditional market structure electricity prices are established by average cost pricing. Average cost pricing reflects a regulated generator's approved costs for less expensive and more expensive supply sources.

In restructured markets, where there

is competition among generators, prices are based on market forces. Buyers and sellers can be brought together to settle a price in a number of ways. One way is a negotiated bilateral arrangement between a generator and a buyer. Another is the formation of a power pool where many buyers and sellers interact to establish the market price.

The power pool approach as adopted in Alberta and contemplated for Ontario employs marginal cost pricing, i.e., the

## Power Strategy Solutions

905.631.4246

[www.cutlerhammer.eaton.com](http://www.cutlerhammer.eaton.com)

Please read more about power strategy solutions on the back cover of this issue.



Cutler-Hammer

EATON



### Gas Turbine Inlet Air FILTERS!

Donaldson filters, made with our proprietary media formulation, Spider-Web<sup>®</sup>, protect your gas turbine from sub-micron particles better than any other filter available! And, as one of our large customers in Canada recently documented, Spider-Web<sup>®</sup> filters can actually help boost turbine output! Models to fit Donaldson and/or other manufacturers' filter systems.

Call for full info today! Be sure to ask for our new *Replacement Filters and Spare Parts* catalog.




## Donaldson


*filtration solutions*

Donaldson Company, Inc.  
P.O. Box 1299, Minneapolis MN 55410  
[www.donaldson.com](http://www.donaldson.com)  
email: [filterinfo@usmail.donaldson.com](mailto:filterinfo@usmail.donaldson.com)  
**Call toll-free: 800-431-0555**





International Transfer of Electricity




B.C./Alberta/U.S. Illustrative Transmission Interconnections

pool price is set by the cost of the last unit of supply required to meet market demand.

An important point about marginal cost pricing is that all producers receive the same price even though their own costs may be lower and they might even have offered supply into the pool at a substantially lower price. This means that, all else being equal, when marginal costs are greater than average costs, the market price will be higher in the restructured environment.

If prices generally equate to marginal costs, prices will change to match the marginal cost of generation, and thus spot prices could be quite volatile. However, prices need not always reflect marginal costs. If the regulatory regime permits, buyers and sellers may negotiate bilateral arrangements for volume, price and time period. Depending on market conditions, the pricing terms could be less than the marginal cost. A well developed forward market, where standardized contracts for the future delivery of electricity are traded according to established rules and regulations, would also provide a similar price risk management function.

Most jurisdictions embarked on restructuring with the anticipation that electricity prices would decline over time, or at least not rise as much as in the regulated environment. The basic driving forces behind that anticipation were technology, which was expected to reduce generation costs, and competition, which was expected to improve efficiency.



Provincial Shares of Electricity Demand

### Time-of-Use (TOU) Rates

As indicated above, a feature of competitive wholesale markets is that prices may fluctuate significantly, subject to market conditions and competitive forces. Further, because electricity cannot be easily stored prices can exhibit pronounced hourly swings.

Consumers can take advantage of these hourly swings by altering their consumption patterns. For example, industrial consumers can reschedule production into off-peak times. Conceptually, residential consumers could also reschedule activities, for example, away from the morning and evening peaks. In the traditional regulated market, utilities use moral

**Continued on page 12**

## EQUI-MAT™

### Personal Protective Ground Grid



#### Portable, lightweight, high performance

The EQUI-MAT™ Personal Protective Ground Grid provides an easy way to help establish an equipotential zone for a lineworker to stand on during various energized and de-energized work practices.



POWER SYSTEMS

#### HUBBELL CANADA INC.

870 Brock Road South • Pickering, ON L1W 1Z8  
Phone: (905) 839-1138 • Fax: (905) 831-6353  
www.hubbellpowersystems.ca

#### HUBBELL POWER SYSTEMS, INC.

210 N. Allen • Centralia, Mo 65240  
Phone: (573) 682-5521 • Fax: (573) 682-8714

#### HUBBELL DE MEXICO, S.A. DE C.V.

Av. Coyoacan No. 1051 • Col. Del Valle • 03100 Mexico, D.F.  
Phone: (525) 575-2022 • Fax: (525) 559-8626

**Continued from page 11**

suasion to perform that function, because there is usually no economic incentive.

A number of observers have pointed out that real-time price signals, i.e., higher prices during peak hours, would be necessary to induce consumers to reduce consumption.

### **Advantages and Disadvantages of Restructuring**

By moving from a cost-of-service environment to the competitive environment implied by restructuring, there are a number of advantages and disadvantages.

Advantages include:

- increased competition, more customer choice, possible service improvements;
- potentially lower costs, if competition results in improved efficiency;
- marginal cost pricing better reflects market conditions and gives better price signals to market participants; and
- trade will tend to promote price convergence between regions: high-price regions could experience lower prices.

Disadvantages include:

- price uncertainty due to changing market conditions;
- possible upward pressures on prices due to increased costs for some market participants (e.g., higher costs of capital because of higher risks);
- higher risks mean uncertainty for new investment compared with cost-of-service regulation;
- marginal cost pricing means more volatility, potential for price spikes;
- trade will tend to promote price convergence between regions: low-price regions could experience higher prices.

### **Summary**

Restructuring of the electricity industry has been taking place in Canada and the U. S. for much of the 1990s. Individual provinces have considered restructuring and have chosen to implement changes to their markets in varying degrees, depending on their circumstances.

*Reprinted from the National Energy Board's Energy Market Assessment "Canadian Electricity Trends and Issues", May 2001. [www.neb-one-gc.ca](http://www.neb-one-gc.ca). ET*

### **Observations, continued from page 9**

RTOs could lead to more north-south trade and increased integration of the U.S. and Canadian electricity markets. To the extent Canadian competitiveness can be maintained, higher export revenue would result. Market integration could also result in upward price pressure in some provinces.

Although market integration may be facilitated by access to current transmission facilities (as expected by the RTO initiative), persistent price differentials between regions with competitive wholesale markets may indicate that new transmission facilities are required.

### **Restructuring of Electricity Markets**

The unbundling of generation, transmission and distribution services is occurring at an uneven pace across the country. Alberta completed its five-year program, introducing full retail access in January 2001, after implementing wholesale access in January 1996. Ontario plans to implement full retail access in May 2002.

At this time, there are no definitive plans to introduce full retail access in the other provinces; the reasons for this vary. In many provinces, it appears that, with the historical record of relatively low and stable prices and the prospect that this will continue to prevail in the near term, there is limited incentive to change the current regulated regime. However, a number of provinces currently provide, or plan to provide, whole-sale access.

A prime motivation seems to be to satisfy the reciprocity requirements of FERC Order 888.

Two main objectives of restructuring are lower prices and more customer choice. Increased competition might be expected to result in lower prices. However, there may also be higher costs associated with the increased risk faced in a competitive market environment, as compared with a regulated environment.

An example would be the increased cost of capital faced by electricity suppliers.

There is substantial debate about whether restructuring will ultimately result in higher or lower prices; however, it is clear that, in any given region, the design of the restructuring program and the supply and demand situation

will be important factors in establishing the eventual outcome.

### **Electricity Prices**

Volatile energy prices do not necessarily mean volatile electricity prices. In all provinces, with the recent exception of Alberta, consumer prices have been generally stable, or have increased by relatively small amounts, over the past several years. This stability is largely the outcome of the provincial regulatory regimes which establish prices on a cost-of-service basis and, in some provinces, the implementation of price freezes. Prices tend to be lower in provinces that generate most of their electricity from hydro resources (e.g., B.C., Manitoba and Québec). A comparison with residential electricity prices in other countries suggests that Canadian prices are among the lowest of the industrialized countries.

Continuing to establish electricity prices on the basis of regulated costs would be a departure from the pricing of other energy commodities, which is based on domestic and international market forces.

To the extent there is a difference between the regulated cost and the market value of electricity, as measured, for example, by the prices of competitive fuels in the same market area or electricity prices in adjacent market areas, electricity consumers and producers may not receive the appropriate price signals for decision-making. A regulated price that is set below market value could result in too much consumption and/or insufficient production, and a price that is set above market value would have the opposite effects.

Growing reliance on market forces in other sectors of the economy and in other electric power jurisdictions in North America is causing Canadian provinces to consider adopting market-based structures.

However, the record of low electricity prices provided, for the most part, by provincially-owned utilities under the traditional structure, and the recent experience with price volatility in California, have caused most provinces to move cautiously toward developing comprehensive restructuring plans.

*Reprinted from the National Energy Board's Energy Market Assessment "Canadian Electricity Trends and Issues", May 2001. [www.neb-one-gc.ca](http://www.neb-one-gc.ca). ET*



# Canada's latest newcomer loves low temperatures



Transformer oils from Nynas never come in from the cold. They don't have to.

Our TFOs have excellent low temperature characteristics while also offering high solubility.

That's only half the story, though.

We immodestly think of ourselves as a pretty talented newcomer in Canada – refining and distributing our own naphthenic oils instead of relying on third parties.

This amounts to a guarantee that Nynas can provide reliable and consistent supplies whenever.

Not for nothing has Nynas become the global market leader for power industries.

We got there by helping customers get the very best out of our naphthenics. A simple philosophy, perhaps.

It works.



Nynas Canada Inc., Suite 610, 201 City Centre Drive, Mississauga, Ontario, Canada L5B 2T4  
Tel.: +1 905 804-8540. Fax: +1 905 804-8543  
Internet: [www.nynas.com/naphthenics](http://www.nynas.com/naphthenics)

## PROTECTION and CONTROL

### IPP Protection:

# Interconnection Transformer Winding Arrangement Implications

By Wayne Hartmann

The increased number of independent power producer (IPP) interconnections for peak shaving and power continuity applications on distribution feeders has increased the interest in, and application of, IPP interconnection protection. When operating IPP generation, known as dispersed generation (DG), is parallel with the utility, the applied interconnection transformer winding arrangement has an effect on what protection is applied to provide utility ground fault detection, and the subsequent separation of the IPP's generator from the utility. This protection and separation of the IPP's DG from the utility is required, so the IPP does not continue to feed into a utility ground fault after the utility has tripped an upstream substation circuit breaker or a line fault-clearing device, such as a recloser. Clearing a utility ground fault from all sources, including any IPPs on the feeder, is necessary to extinguish the arc. A typical circuit is illustrated in Figure 1.

After the arc is extinguished, typically an automatic reclosing sequence (by the breaker or recloser) is applied to test the feeder; it then remains closed if the fault was transient




Figure 1: Ground Fault Between Utility Substation and IPP

in nature. After the reclosing cycle is deemed successful (the reclaim timer expires), any IPPs on the feeder are then clear to attempt parallel DG operation with the utility.

The interconnection transformer winding arrangement can be defined as the type of winding that is applied to the primary, or utility side, and the secondary, or IPP side, of the transformer. Several winding arrangements are possible, all requiring an understanding of the impact each arrangement will have on the utility's protection, the IPP's protection, and power system operation. The common IPP interconnection transformer winding arrangements are shown in Figure 2.




Figure 2: Common IPP Interconnection Transformer Winding Arrangements




Figure 3: Ground Fault at Various Locations on Distribution System with IPP



**Response POWER** The Leader In Virtual Generation

## GENERATORS...

Would you like to improve your pricing strategies?

Do you need real-time notification of system load changes and the values of your generation?

Response Power offers you superior market intelligence to manage your power system outputs for maximum revenues and minimum cost.

You can receive customized monitoring and notification of the factors that affect the prices for your electricity.

Within a few hours you can be set up to take advantage of this new opportunity.

*We offer software & hardware solutions that give you control.*

Call today for more details  
**780-429-4774**  
 or visit our website at...  
[www.responsepower.com](http://www.responsepower.com)  
 ... for a FREE trial demo






Figure 4: Voltage Shift for Ground Faults on Ungrounded Systems




Figure 5: Use of Displacement Voltage and Over/Undervoltage for Ungrounded System Ground Fault Protection

If the generation at the IPP site is retrofitted into the facility, the usual transformer arrangement is delta-wye (grounded). This arrangement is typically chosen to provide isolation for utility for ground faults in the IPP's facility, and to supply a ground source for the IPP facility.

Examining each of the interconnection transformer arrangements, and placing ground faults on the circuit illustrated in Figure 3, the pros and cons of each may be explored.

### Delta-Delta

#### Pros:

- Doesn't provide ground fault backfeed for fault at F1 & F2.
- Does not provide ground current contribution from Breaker 1 for a fault at F3.

#### Cons:

- Can supply the feeder circuit from an ungrounded source after substation Breaker 1 trips and causes overvoltage.
- Does not supply a ground source for IPP facility.

### Delta-Wye (grounded)

#### Pros:

- Does not provide ground fault backfeed for fault at F1 & F2.
- Does not provide ground current contribution from Breaker 1 for a fault at F3.
- Supplies a ground source for IPP facility.

#### Cons:

- Can supply the feeder circuit from an ungrounded source after substation Breaker 1 trips and causes overvoltage.

### Wye (ungrounded)-Delta

#### Pros:

- Does not provide ground fault backfeed for fault at F1 &




Figure 6: Typical IPP Interconnection Protection Application — Grounded Interconnection Transformer Primary (Utility) Winding




Figure 7: Typical IPP Interconnection Protection Application - Ungrounded Interconnection Transformer Primary (Utility) Winding

**Continued on page 16**

## ELIMINATE DOWNTIME

[www.ampsabundant.com](http://www.ampsabundant.com)



We're the Power Semiconductor specialists with one goal in mind — ELIMINATE EQUIPMENT DOWNTIME. OEM or obsolete parts crossed. Call us at 1-800-233-0559 and let us provide you with the service you deserve.

**AA AMPS ABUNDANT**

(Amps Abundant is not affiliated with any OEM and does not provide parts or service on their behalf.)

11125 Knott Avenue, Suite D, Cypress, CA 90630

Tel: 714-379-7308 Fax: 714-379-2704

For even faster service, call us toll-free: 1-800-233-0559

**Continued from page 15**

F2.

- Does not provide ground current contribution from Breaker 1 for a fault at F3.

**Cons:**

- Can supply the feeder circuit from an ungrounded source after substation Breaker 1 trips and causes overvoltage.
- Does not supply a ground source for IPP facility.

**Wye (grounded)-Delta****Pros:**

- Does not supply ground current from Breaker 1 for faults at F3.
- Does not cause an overvoltage for ground fault at F1.

**Cons:**

- Provides an unwanted ground current for supply circuit faults at F1 and F2.

**Wye (grounded)-Wye (grounded)****Pros:**

- Does not cause an overvoltage for ground fault at F1.
- Supplies a ground source for IPP facility.

**Cons:**

- Provides unwanted ground current for supply circuit faults at F1&F2.
- Supplies ground current from Breaker 1 for faults at F3.

Note: First winding is utility primary, second is IPP secondary

The first three transformer winding configurations provide a focus on interconnection protection, (and all configurations provide an ungrounded utility primary winding,) but they require a different utility system ground fault protection method than the last two transformer winding configurations, which provide a grounded utility primary winding.

When employing a grounded utility primary winding, if the utility opens its substation breaker or line recloser, the IPP's DG can backfeed the distribution line, and a ground current is available at the interconnection transformer which is detectable by employing ground overcurrent elements. On the primary (utility) side of the transformer, a transformer neutral ct may be the source for directional or non-directional ground current protection (51N or 67N).

On the secondary (IPP) side of the transformer, phase undervoltage elements may be applied to detect utility ground faults, as the resultant voltage drop is measurable across the interconnection transformer while the utility has not yet cleared the ground fault. The measured secondary (IPP) side voltage will also drop if the IPP is sourcing the fault. For delta secondaries, in addition, voltage controlled or restrained overcurrent elements (51VC and 51VR), sometimes directionalized for greater sensitivity (67 supervision) may be employed. For grounded wye secondaries, ground overcurrent (51N) or directional ground current (67N) elements may be employed as the zero sequence current commutates across the grounded wye-grounded wye transformer.

When employing an ungrounded utility primary winding, if the utility opens its substation breaker or line recloser, the IPP's DG can backfeed the distribution line. As the ungrounded delta winding does not commute zero sequence current to the secondary, conventional ground relays applied on the



## PUT POWERTECH'S EXPERTISE TO WORK FOR YOU

Transformers are vital components in both the transmission and distribution of electrical power. Powertech is helping utilities, power producers and distributors worldwide maximize transformer performance and reliability.

Powertech uses state-of-the-art equipment and diagnostic tools to detect incipient faults in oil-filled electrical equipment. Cost-effective insulating oil analysis minimizes downtime and extends the life of your transformer.

We also provide leading-edge research services. Areas where we can help:

- Determining contaminants and impurities in transformer oil
- Comprehensive dissolved gas in oil (DGA) and insulating fluids analyses
- Life assessment and life extension
- Consultation and investigation of field problems
- Analyses of sulfur hexafluoride (SF<sub>6</sub>) gas for contaminant and decomposition products

Call 604 590-7500

[www.powertechlabs.com](http://www.powertechlabs.com)

email: [info@powertechlabs.com](mailto:info@powertechlabs.com)

**Powertech** 

primary neutral will not detect ground fault current. This is because the ungrounded winding does not provide a ground source. The phase and ground protection on the secondary (IPP) side of the interconnection transformer will not be able to detect and clear the utility feeder ground fault supplied by the ungrounded source. Fortunately, there are methods employing voltage protection that can detect a ground fault supplied from an ungrounded source.

To detect and clear the utility ground feeder ground fault sourced from the ungrounded primary (utility) side winding, a protection scheme is applied that uses one of two options:

The displacement voltage across a broken delta transformer on the utility's system (primary side of the interconnection transformer): This method utilizes the fact that when a corner of the delta system is grounded, the normally balanced voltage triangle is shifted as shown in Figure 4. The resultant voltage across the broken delta potential transformer is three times the line-to-ground voltage (secondary).

Over/under voltage of a single phase measured line-to-ground voltage on the utility's system (primary side of the interconnection transformer): This method takes advantage of the fact that when a phase of the delta system is grounded, the grounded phase falls to zero volts, as it is now the ground reference. The other two phase voltages rise to line-to-line values. The resultant voltage across a single line-to-ground connected potential transformer will be a detectable undervoltage or overvoltage (1.73 times the line-to-ground secondary value) depending on which phase has the ground fault. Both of these methods are shown in Figure 5.

When used together with the other protections typically employed for IPP interconnection protection, we have two basic schemes, one for grounded interconnection primary (utility) windings, as shown in Figure 6, and one for ungrounded interconnection primary (utility) windings, as shown in Figure 7.

To summarize, the interconnection transformer winding arrangement applied has implications on the protection utilized at the IPP's facility; it also has possible impacts on distribution system protective elements. There is no single 'best' connection type or universally applied arrangement.

Attention must be paid to winding and utility side grounding so the proper IPP ground fault backfeed protection

may be applied and other coordination issues can be realized.

## References

- [1] ANSI/IEEE Std. 1001-1988, 'Guide for Interfacing Dispersed Storage and Generation Facilities with Electric utility Systems.'
- [2] IEEE P1547, Draft Standard for Distributed Resources Interconnected with Electric Power Systems.
- [3] Mozina, C.J., 'Interconnection

Protection of Dispersed Generators in the New Millennium', Texas A&M University Conference for Protective Relay Engineers, College Station, Texas, April 11-13, 2000.

- [4] M-3410 Intertie/Generator Relay Instruction Manual, Beckwith Electric, 2001.

Wayne Hartmann is Applications Manager for Protection and Protection Systems at Beckwith Electric Co. Inc. WHartmann@beckwithelectric.com. **ET**

# pain relievers



**Unresolved  
challenges,  
stubborn  
problems,  
finally, relief  
that lasts**



**KINECTRICS**

The North American energy sector is searching for a prescription that will improve performance and deliver a healthy bottom line. We are Kinectrics and we believe we have it. Our people come equipped with stethoscopes so they can listen, learn, and understand your pain. They are experts, who leave no stone unturned in their search for a remedy that's good for you, your customers, and investors. We are the scientists and engineers that kept Ontario Hydro fit and healthy for over 85 years. As a vibrant independent company, Kinectrics is focused on delivering innovative solutions, solid results, and pain relief that lasts.

For more information  
please call: 416.207.6000  
or visit our website  
[www.kinectrics.com](http://www.kinectrics.com)

KINECTRICS ideas into energy



## Infrared Inspection Just Got EASIER.

Introducing the NEW **ThermaCAM® PM 695**  
Thermal Imaging System


### See it.

Find problems quickly with the new **ThermaCAM PM 695** fully automated infrared inspection system. With its thermal and built-in visual camera, you can easily detect electrical and mechanical problems far in advance of failures and prevent costly power outages.



### Measure it.

Sometimes seeing a problem thermally just isn't enough. You need to quantify temperatures to make effective maintenance decisions. The **ThermaCAM PM 695** delivers accurate temperature measurements that allow you to quickly determine "how hot is hot."



### Report it.

Document inspection results automatically with the **ThermaCAM PM 695**. We simplify the process and make your job easier.



5230 South Service Road Unit 125  
Burlington, ON L7L 5K2  
(905) 637 5696  
Email [IRCanada@flir.com](mailto:IRCanada@flir.com)

1 (800) 613 0507  
[www.flir.com](http://www.flir.com)

**ThermaCAM® PM 695**  
**One Camera. Total Solution.**

## POWER QUALITY Q&A

# Answers to Frequently Asked Questions About Power Quality

By David Windley, P.Eng., C.I.M.

### Question:

We are constructing a new building where sensitive electronics will be installed. If the electrical distribution system is installed according to the Electrical Safety Code, will this be sufficient from a power quality standpoint?

### Answer:

The Electrical Safety Code is a minimum standard which defines the method and materials that must be used in the installation of electrical equipment and the wiring of machinery and facilities. Its prime focus is safety. When an inspector is reviewing an installation, he or she is looking for conformity with the Code and more specifically correct wire sizing, fusing, clearances, and grounding. If we look closely at the Code, there is very little that concerns itself with the quality of the power we hope to receive.

Therefore, if we use the Code as our specification for defining power quality installation practices, we will be quite disappointed with the results.

So how do we get the results we want; a safe reliable power system that works with our sensitive electronic equipment? We have to define what is needed to achieve our goal and communicate it to those performing the installation work. One way to do this is to find an electrical engineer or other experienced professional who knows power quality issues and how to mitigate the potential problems. Engage them to write a specification that details the materials and methods that cover all your power quality concerns. Include this specification in all your electrical specification packages for bidding.

In this way, the installation contractor knows exactly what is expected, can bid accurately, and will provide you with an installation that will be reliable and trouble-free. Of course, as with any contract, you must ensure that the installation follows the specifications.

In the end, you will get the system you want and will find that the extra cost involved is minimal.



### Question:

What is the best type of Uninterruptible Power Supply (UPS) to use for my Computer Centre?

### Answer:

Typically, for computers we are trying to protect against a data loss from momentary outages. For longer-term outages, we are trying to buy time so that open files can be closed and our operating system brought down in an orderly fashion.

One available type is a Stand-by type system. In this type, the computer runs normally from a clean AC line. This AC supply also charges a set of batteries that remains in a stand-by mode. If an outage occurs, a static (or solid state) switch connects the battery through an inverter to the computer load.



When the AC line comes back on, the switch reverts back to its normal position and the computer is fed from the AC power supply. With this type of system, there is a short discontinuity of power during switching even though the static switch reacts very quickly. This switching may affect the computer hardware or the integrity of the data.

Another, more preferable solution would be to use a Floating type system. In this type a reliable AC source feeds a rectifier or battery charger which holds a charge on a set of batteries. An inverter uses this DC power to synthesize an AC waveform that is used to power the computer. Therefore, the computer is 'floating' or drawing inverted power from the batteries under normal circumstances. Hence, when a loss of AC power occurs, the computer continues to operate on the batteries without any switching or discontinuity. When the power returns, normal operation resumes.

Regardless of the type of UPS selected, it is vital that the UPS provide a clean sinusoidal output. A higher end UPS will do this. A check of its specifications will confirm this. A lower end UPS designed for general back-up service will give a rougher, if not square wave type output. Transients and harmonics associated with a non-sinusoidal output may create undesirable power quality effects.

Looking at the big picture, there may be other things to consider. Are there other systems that may affect the computer's operation such as air conditioning systems? If these cease to operate during power failures, will they cause a computer failure? Some strategy may have to be developed for them.

*David is the President of Wintek Engineering. You can forward your questions or comments to him at [wintek@wintek-eng.com](mailto:wintek@wintek-eng.com).*

*Some of these questions will be addressed in future issues of Electricity Today's Power Quality Question & Answer Column. **ET***

# FIRST LINE PROTECTION

WHEN COMMUNICATIONS ARE THREATENED, THE TELELINE ISOLATOR IS YOUR FIRST LINE OF DEFENSE.

In this ever more competitive world, utilities rely increasingly on communications. Quality, safety and reliability are the watchwords. But lightning strikes and high voltage surges can wreak havoc with wire-line circuits. Arm yourself against this damage. Contact us and find out why, over the past 20 years, Positron has become the first name in isolating critical circuits.



[www.positronpower.com](http://www.positronpower.com)  
1-888-577-5254

**POSITRON**

Teleline Isolator for  
Wire-line Communications

## GENERATION

# Creating a Potential \$5 Million Revenue Gain From Hydropower Turbines Using Computational Fluid Dynamics Simulations

By Bernard Massé

CFD simulations helped engineers at Hydro-Québec make design changes that will generate revenue gains of up to \$5 million in twelve hydropower turbines. By shifting the maximum efficiency point to raise the power output by 7.8 megawatts and by raising the weighted efficiency of the turbine by 1.6 per cent, the changes will produce revenue gains of between \$200,000 and \$500,000 per year for each turbine. The exact amount depends upon the grid demand. These revenue gains have already been validated in one turbine and plans are being made to implement the design changes on the other eleven turbines. These gains were made by modifying the runner at the blade trailing edge to eliminate a large eddy in

the draft tube elbow that was discovered to be reducing efficiency of the turbines. The eddy was discovered and the design changes were validated by using CFD in order to provide researchers with a clear understanding of fluid flows throughout the turbine.

Hydro-Québec is a world leader in generating green energy, with over 31,400 MW of installed capacity in 1998 and ranks among North America's largest distributors of energy. It serves 3.5 million residential, commercial, institutional and industrial customers in Québec. In addition, it supplies nine municipal systems, one regional cooperative, and some fifteen electric utilities in the Northeastern United States, Ontario, and New Brunswick. Since

obtaining a marketer's license from the Federal Energy Regulatory Commission, it also makes direct sales, at market prices, to American power wholesalers, including public utilities, municipalities, resellers, and large industrial consumers in the United States. Its 1998 sales totaled 161.4 TWh, with Québec markets accounting for more than 88 per cent (142.8 TWh) and sales outside Québec for nearly 11.5 per cent. The company is publicly owned with a single shareholder, the Québec government.

## Less efficiency than expected

A Hydro-Québec power plant, commissioned in the early 1980's, was operating with less hydraulic efficiency than was expected from the reduced scale model tests conducted by the manufac-

## Allen-Sherman-Hoff

185 Great Valley Parkway • Malvern, Pennsylvania 19355

1-888-ASH-PARTS (1-888-274-7278) in USA • (610) 647-9900 Internationally • Fax: (610) 648-8724

Our name is our business.  
www.a-s-h.com




Figure 1: Reduced losses in the draft tube (before modification).




Figure 2: Reduced losses in the draft tube (after modification).



turer and confirmed by an independent test stand. When the power plant was originally built, there was no way to determine what went wrong in the design and fabrication of the 12 identical turbines used in the plant. Because of the tremendous advances since that time in numerical simulation tools, it was decided to take another look at this problem with the goal of finding the cause and, ultimately, a solution to raise the efficiency of the turbines. CFD, the technology used in this simulation, involves the solution of the governing equations for fluid flow at thousands of discrete points on a computational grid in the flow domain. When properly validated, a CFD analysis allows engineers to determine the direction and speed of flow at any point in the flow domain. Unlike a physical model, the geometry of the CFD model can be changed quickly on the computer and re-analyzed to explore different options in project design or operation conditions.

Fluid flow simulations were conducted in the whole turbine from the water intake through the penstock, the spiral casing, the distributor, the runner, and the draft tube. To compute the flow inside a complete turbine, iterations are required to link together the components, distributor, runner, and draft tube. Velocity profiles, turbulence parameters, and pressure distributions must be transferred from one component to the other in order to assure a coherent flow through the entire turbine. For a given operating condition, the mass flow and wicket gates angle are specified to compute the distributor flow field. This gives the velocity profiles and turbulence parameters to be used as runner inlet flow conditions. The runner flow is then computed and outlet profiles are used as draft tube inlet conditions. The pressure is then computed as the flow is solved in the draft tube and is used as runner outlet boundary conditions to recalculate the flow. The same is done with pressure at the distributor outlet.

### Eliminating several areas from consideration

Fluid flow in the water intake and in the penstock is responsible for the flow profile entering the spiral casing. Questions were raised about the velocity profile at the entrance of the spiral casing due to the presence of an elbow just upstream and also because the flow at the water intake itself arrives at various angles. Experimental measurements were available on a scaled model of the

water intake where the shape of the reservoir had been reproduced and the inlet angle could be changed. The CFD analysis correlated well with the model measurements and did not show any anomalies, leading analysts to believe that the efficiency problem was not related to the water intake or the penstock.

The flow field was simulated in the spiral casing to check for problems. The contour of radial velocities generated by the analysis indicated that the flow at the runner inlet was uniform along the circumference. In addition, no problematic flow pattern was seen in the spiral casing. The problem was then suspected to reside in the turbine itself. As the flow was seen to be uniform in the distributor, a section of the distributor was modeled for flow simulation and loss computations. In order to investigate the flow in the runner, two hydraulic passages were measured on site. A mechanical digitizing arm was used to measure the surface data of critical parts, such as leading and trailing edges and complex surfaces of the blade.


### Selecting FEA-based CFD software

Hydro-Québec researchers selected the FIDAP CFD code from Fluent

Incorporated, Lebanon, New Hampshire, as one of their modeling and analysis tools. This software package uses the finite element approach and has the advantage of using non-structured grids. Non-structured grids provide considerably greater flexibility in modeling the complex and irregular geometries involved in hydropower turbines. Non-structured grids also automate the otherwise impracticably tedious process of fitting elements to the complex geometries used in complex areas such as the draft tubes. Care was taken to ensure good mesh quality, especially near the walls, which are responsible in large part for the losses. Using the iterative approach described earlier, several turbine operating conditions were computed.

The simulation in the turbine showed a large eddy in the elbow. Further analyses led researchers to conclude that this phenomenon was the main cause of the efficiency problem. The eddy arises just before the peak operating point and up to the maximum load. It is related to inappropriate flow at the runner exit. The runner-draft tube interaction is responsible for most of the

**Continued on page 22**




Management Systems Registration and Training

**In These Changing Times, Partnership With Your Registrar Has Never Been More Critical!**

If management system registration is one of your company's goals, call us. If superior service and attention to your company's needs are important to you, call us. If new business opportunities here at home or around the globe are in your plans, call us. We'll give you a world of reasons to give us your business.

Registration Services for all your business needs.  
Please call Client Services at (604) 244-6800.



A DIVISION OF CSA GROUP

### Continued from page 21

losses. However, another smaller eddy was detected in the runner, near the leading edge and the crown on the pressure side of the blade.

### Reducing the losses

To reduce the losses, the water flow between the runner and the draft tube had to be improved. Researchers chose to modify the runner outlet and designed a new trailing edge. A parametric study was conducted on the draft tube flow to determine the influence of the inlet flow parameters on its performance.

Several blade cuts and extensions were tried to modify the critical parameters. Once the draft tube flow was optimized, the flow in the runner was examined to reduce, if possible, runner losses at the same time. The researchers arrived at a solution that reduced hydraulic losses in the runner as well as the draft tube at the maximum efficiency point.

The efficiency measurements on the prototype, measured by an independent team, showed a significant increase in turbine efficiency at all operating conditions. The gain is about 1.5 per cent at the peak and increases as the operation moves to the maximum power point. At the maximum efficiency point, the gain



Figure 3: Runner modification at power plant.

is due to the improved flow both in the runner and in the draft tube elbow. In the draft tube, analysis results showed that the eddy in the elbow was gone.

In the runner, the effect of the eddy is reduced.

The maximum efficiency point is shifted to the right and gives an additional 7.8 MW to the 195MW nominal

unit with 1.5 per cent more efficiency.

### Effects of new design on erosion

Researchers also looked at the effects of the new design on cavitation erosion. The CFD results indicated an increase of inlet cavitation with the modified runner. Measurements using a vibratory cavitation detection method before and after modification indicate a possible increase of 30 per cent in erosion at the maximum efficiency point and an increase of 85 per cent at maximum power. This increase was not considered to be a serious problem since the original runner cavitation level was low. The increase in efficiency far more than compensates for the expected small increase in maintenance costs.

The modifications were first applied to a single Francis turbine. The modified turbine provided more than the increase in efficiency that was predicted by the analysis. In less than a year of operation, this improved efficiency has already paid for the \$200,000 cost of the modifications. Hydro-Québec management is currently making plans to implement the modifications on the other eleven turbines for this power plant. Planning is also in progress to use CFD to improve turbine efficiency at other power plants.

This application provides an excellent illustration of how CFD simulations can identify hydropower problems and help develop alternatives to improve machine performance.

*Bernard Massé is Hydraulic Machines Team Leader with the Hydro-Québec Institute of Research (IREQ). ET*

## RADIODETECTION CANADA

A United Dominion Company

### Locate With Confidence



### Information From Underground

- Accurate locating and fault locating even in severely congested areas.
- Locate and depth measurement confirmation.
- Software driven - upgradable.
- Rugged, weatherproof housing
- Electronic marker systems
- GPS compatible-automated mapping capability.
- Complete On site training across Canada.
- NEW Bicotest Fault Detection Equipment

Call Radiodetection Canada toll free for the name of your local distributor:

**1-800-665-7953**

[www.radiodetection.ca](http://www.radiodetection.ca)

# PRODUCT SHOWCASE



## **NYNAS CANADA INC. Naphthenic Transformer Oil**

Nynas Canada Inc. is a producer of naphthenic transformer oil. We refine our oil from Venezuelan naphthenic crude. Nynas Nytro 10 C and Nytro 10 CX exceed the CSA-C 50 Class A type I and type II specifications, respectively. Nynas Nytro 10 GBN exceed the CSA C-50 Class B type I specification, while both Nynas Transformer Oil X and Nytro 10 GBXT exceed the CSA C-50 Class B type II specification.

For more information contact:

Nynas Canada Inc.  
201 City Centre Drive, Suite 610  
Mississauga, ON L5B 2T4  
Tel: (905) 804-8540  
Fax: (905) 804-8543



## **CABLE MASTER INC. 3M/AEMC/HDW Regional Distributor**

We specialize in Training and Sales of a full range of 3M/HDW/AEMC equipment

- 3M Dynatel Cable/Pipe/Fault Locators
- 3M EMS Markers and Locators
- 3M Confined Space Monitors
- HDW Fault Locating Equipment and TDRs.
- New, Demo or refurbished units
- Lightweight, compact and rugged
- ISO 9002 Registered
- We have 35+ years experience
- Complete line of AEMC instruments
- **Hi-Pot testing 0-130kv DC**
- **Fault locate all types of cables**

For Sales/Training/Contract Locates:

Toll Free: 877-715-7303

Tel: (416) 804-8799

Fax: (905) 715-7305

Email: [cablemaster@home.com](mailto:cablemaster@home.com)

Web: [www.cablemasterinc.com](http://www.cablemasterinc.com)



## **POSITRON The Total Reach Option**

Positron is pleased to announce that our new improved ISDN Adtran Total Reach Card is currently available.

The 751333A offers the same functionality as the 751333 but with the advantage of the ISDN 56K Adtran Total Reach. The 751333A now has a new transformer built with an expanded bandwidth to accommodate the total reach requirements.

The ISDN card fits into any slot of the three, five and eight card shelves.


The Plug-in Card provides high voltage isolation between an ISDN line and the network terminator (NT) equipment at the customer's location. It provides for ground -24 V dc, -48 V dc or floating 130 V dc input.

If you would like any additional information please contact us:

Positron

Tel: 1-888-577-5254

Email: [positronpower@positron.qc.ca](mailto:positronpower@positron.qc.ca)  
[www.positronpower.com](http://www.positronpower.com)



## **THE CONKLIN SHERMAN CO. Condenser Tube Plugs Adjustable and Push Pull Type Plugs Over 1 Million Sold**

Ideal for electric generating power plants. "Condenser tube plugs" are used for plugging condenser tubes. They are easy to install and save time and money.

The adjustable plug is a molded rubber plug with a brass insert mechanism. Expand it, install it, reverse the action and get a tight seal. Use it again and again. The push pull plug is all rubber, simply push it in. Plugs are available in sizes from .530 O.D. to 2.035 O.D.

For information contact:

The Conklin Sherman Co.  
59 Old Turnpike Road PO Box 188  
Beacon Falls, CT, USA  
Tel: (203) 881-0190  
Fax: (203) 881-0178  
[www.conklin-sherman.com](http://www.conklin-sherman.com)



## **WINTEK ENGINEERING LTD. Electrical Engineering Solutions**

Senior Electrical Engineers providing practical, cost-effective solutions to your power quality, control and safety concerns.

- Analysis
- Automation
- Co-ordination
- Design
- Documentation
- Plant Support
- SCADA
- Training

Call us. We can help.

Tel: 1-866-WINTEK1

Fax: (519) 884-5333

e-mail: [wintek@wintek-eng.com](mailto:wintek@wintek-eng.com)

[www.wintek-eng.com](http://www.wintek-eng.com)



## **AMPS ABUNDANT Complete Selection of Power Rectifiers and Thyristors**

Equipment down for lack of the proper Power Semiconductor? Obsolete, discontinued, hard to find? Amps Abundant specializes in a complete selection of power rectifiers and thyristors (SCR). We offer equal to or better than the original device. Savings up to 70 per cent. Stock over 95 per cent of the time. Our staff has over 150 years of combined experience in power semiconductors.

For more information contact:

Amps Abundant

Tel: 1-800-233-0559

Fax: (714) 379-2704

[www.ampsabundant.com](http://www.ampsabundant.com)



# PRODUCT SHOWCASE



## INTERNATIONAL INFRARED CAMERA SALES AND LEASING

**Mikron 7102**  
**Mikron 5104**  
**Agema 550 Elite**

For more information:

Tel: (604) 516-6646

Fax: (604) 516-6674

Email: [Cameras@infraredsales.com](mailto:Cameras@infraredsales.com)

Web: [www.infraredsales.com](http://www.infraredsales.com)



## CUTLER-HAMMER Products and Services

Cutler-Hammer, a part of Eaton Corporation, is a worldwide leader providing customer-driven solutions. From power distribution and electrical control products to industrial automation, Cutler-Hammer utilizes advanced product development, world-class manufacturing, and offers global engineering services and support.

For more information on Cutler-Hammer products and services, call 1-800-525-2000, for engineering services call 1-800-498-2678, or visit our web site at [www.cutlerhammer.eaton.com](http://www.cutlerhammer.eaton.com)



## HUBBELL POWER SYSTEMS New Fargo Wedge Deadend

The Fargo GDW 2000 Series Wedge Deadend offers five product improvements that make the deadend easier and faster to install. The newly designed Parallel Legs allow for easier passage of conductor and installation of larger conductor. Staked Jaw Keepers hold jaws in place and permanently captivate jaw set. Interlocking Die Cast Jaws provide a positive locking action and movement. The Pulling Eye has been repositioned for easier access and sagging of conductor. A permanent Mold Body Casting gives higher strength with tighter tolerance control. Fargo GDW Deadends were first introduced in 1993. Fargo wedge deadends are recognized for their cost savings compared to bolt-type deadends.

For more information contact:

Hubbell Canada Inc.

Tel: (905) 839-1138

Fax: (905) 831-6353

Email: [InfoHPS@Hubbellonline.com](mailto:InfoHPS@Hubbellonline.com)



## LIZCO SALES Electrical Power Equipment Specialists

BUY-SELL-LEASE-RENT

New Oilfilled Transformers — IN STOCK!

New "TLO" Unit Substations

13.8kV and 27.6kV

New Station Class Transformers

44kV and 27.6kV

New Padmount Transformers

27.6kV / 13.8kV / 4.16kV

Large "in stock" inventory on website

- New/New surplus/refurbished
- Oilfilled and dry type transformers
- High and low voltage switchgear

For more information contact:

Toll Free #877-842-9021

Tel: (519)842-9021 Fax: (519)842-3775

24 hr. Emergency Page # (519) 675-7005

Email: [xfmr@lizcosales.com](mailto:xfmr@lizcosales.com)

[www.lizcosales.com](http://www.lizcosales.com)



## CITEL INC. Surge Protectors

- AC surge protectors for 110VAC, 220VAC, 480VAC
- Data line surge protectors for RS232, RS485, T1/E1, ISDN
- RF Coaxial Protectors
- Ideal to protect RTUs, PLCs, SCADA, Radios
- DIN Rail and Panel Mount

For more information contact:

CITEL, Inc.

1515 N.W. 167th St., Ste. 5-223

Miami, FL 33169

Tel: 305-621-0022

Fax: 305-621-0766

[www.citelprotection.com](http://www.citelprotection.com)

E-mail: [citel4u@ix.netcom.com](mailto:citel4u@ix.netcom.com)

## Powertech

## POWERTECH Insulating Oil Laboratory

We are a technology company providing testing, consulting and research services to the electric and natural gas industries, their customers and suppliers.

Our Insulating Oil Laboratory can help you with the maintenance of your transformer.

We test transformer oil for:

- Dissolved gases and moisture
- Oil quality
- Furan analysis
- Degree of polymerization

ISO 9001 Registered

For more information contact:


Powertech Labs Inc.

(604) 590-7500

[www.powertechlabs.com](http://www.powertechlabs.com)

email: [info@powertechlabs.com](mailto:info@powertechlabs.com)

# PRODUCT SHOWCASE



## ACADEMY OF INFRARED THERMOGRAPHY

### Infrared Thermography Training

AIRT trains infrared thermography to individuals and companies, worldwide. Academy offers basic operator training to Level 3 Infrared Certification.

Level I Infrared Certification

Jan 14-18 — San Diego, CA

Feb 4-8 — Houston, TX

Feb 11-15 — Toronto, ON

Feb 25-Mar 1 — Orlando, FL

Level II Infrared Certification

Jan 21-25 — San Diego, CA

Level III Infrared Certification

Apr 22-25 — Seattle, WA

Electrical Infrared Certification

Apr 15-19 — Toronto, ON

For more information contact:

Academy of Infrared Thermography

Tel: (604) 516-6646 Fax: (604) 516-6674

AIRT@InfraredTraining.NET

www.InfraredTraining.NET



## ANNOUNCING WIRE SERVICES

### A New Initiative of Manitoba Hydro and TerraPoint

Developed to service the electric utility industry, WIRE Services provides a full range of transmission line

VERIFICATION and RE-RATING services utilizing Airborne LiDAR scanning LASER technology.

Need to VERIFY the exact maximum thermal operating limit?

Need to study the feasibility of RE-RATING?

**Call us at 204-480-5800 or email info@wireservices.ca**



## G.T. WOOD COMPANY LIMITED High Voltage Electrical Contractor

- High Voltage Preventative Maintenance
- Transformer and Switchgear Repair
- Infra Red Thermography Inspections
- Engineering Design Studies
- Substation Design and Build
- Harmonic Analysis
- Power Factor Correction
- Cable Locates and Repairs
- Sales of New and Pre-owned Equipment
- Supply of Temporary Substations
- PCB Management

24 HOUR EMERGENCY SERVICE

For additional information contact:

Toll free: 1-800-305-2036

Tel: (905) 272-1696

Fax: (905) 272-1425

Email: sales@gtwood.com

www.gtwood.com



## CANADIAN ELECTRICAL CODE Understand and Use

### The Code Book Like An Expert

The "Canadian Electrical Safety Code" Course for Apprentices, Journeymen, Engineers, Designers and Supervisors.

Available as an:

ON-SITE WORKSHOP

"DO YOUR OWN TRAINING" package

Individual "SELF STUDY" program

on CD ROM, via EMAIL, or in PRINT

Call now for a brochure or visit our website for details:

Onsite Electrical Training Inc.

PO Box 1594

South Porcupine, ON P0N 1H0

Tel/Fax: (705) 235-5071

email: onsite@vianet.on.ca

http://maxpages.com/onsitetraining



## FLEX-CORE

### Current Transformers, Transducer & Accessories — New Catalog 2007

172 page catalog featuring split-core and solid-core current transformers, potential transformers, electrical transducers for AC and DC applications, signal conditioners, signal converters, analog and digital panel meters, analog and digital switchboard meters, digital counters, current probes, current relays, current switches, shunts, shunt switches, selector switches, shorting terminal blocks, fuse blocks, data loggers, multi-function power meters, KWH sub-metering systems and analog to pulse converters.

For more information contact:

Flex-Core

6625 McVey Blvd

Columbus, OH 43235

Tel: (614) 889-6152 Fax: (614) 876-8538

Email: flexcore@email.msn.com



## KABAR INDUSTRIES

### Kabar Anchoring System

Kabar has a complete line of Anchoring; consisting of Power Installed Screw Anchors, Cross Plate Anchors, Expansion Anchors, Wedge and Rock Slide Anchors.

Kabar is able to meet your varying anchoring needs.

Product made in Canada.

For more information contact:

Kabar Industries

Tel: (905) 478-8983

Email: kabar@kabar-almat.com

# PRODUCT SHOWCASE



## ELECTRO INDUSTRIES/GAUGETECH Communication Multiplexor and Telephone Line Switch Substation Multiplexor SM1-16

Electro Industries designed this superior Substation Multiplexor to provide a low-cost and dependable solution for substation telecommunication applications. This unit allows users to communicate to multiple devices within a substation more reliably and with faster throughput.

This unit multiplexes 16 serial ports to one master port providing the ability to communicate with multiple serial RS485 or RS232 devices. This switch uniquely offers Modem Manager technology that buffers the phone line making communication more reliable.

For more information contact

Electroindustries/GaugeTech

Tel: (516) 334-0870 Fax: (516) 338-4741

Website: [www.electroind.com](http://www.electroind.com)

Email: [sales@electroind.com](mailto:sales@electroind.com)



## ELECTRICITY FORUM Transmission & Distribution Product Directory and Buyers Guide On the Internet

Looking for a fast way to find manufacturers and suppliers of electrical products and services? Then visit the New Transmission and Distribution Product Directory Buyers Guide at the Electricity Forum Web Site. This guide covers over 1,000 product listings and up-to-date information on the companies that make these products.

Access the Guide at:

[www.electricityforum.com](http://www.electricityforum.com)


For information about listing your

company on the guide, contact:

The Electricity Forum

Tel: (905) 509-4448

Fax: (905) 509-4451



## CADTEK INC. Schematic, Cabling and Enclosure Layout and Automatic Wire Routing Applications

Easy Object orientated Windows design application for Electrical Engineers to create fully integrated Schematic drawings, Cable and connector harness diagrams and Intelligent Panel layouts.

- Completely scalable solutions ranging from small control applications through to large power stations and transportation systems.
- Automatic creation of schematic drawings with dynamic cross referencing of devices and off drawing connections.
- Automatic generation of user definable reports, detailing materials, terminal schedules, wire lists including lengths, cut lengths and conduit runs.

For more information contact:

Cadtek Inc., Tel: (570) 476 5700 ext 208

Email [Paul.Harvell@cadtek.com](mailto:Paul.Harvell@cadtek.com)

[www.Cadtek.com/e3series](http://www.Cadtek.com/e3series).



## MIDTRONICS Micro Celltron

The Midtronics Micro Celltron is a state of the art electronic battery tester utilizing conductance technology (applying a low frequency AC voltage signal of known frequency across the battery and observing the current response) to measure battery state of health. Measurements provided by tester include conductance readings in Siemens units, percentage of referential conductance value, and voltage.

For more information contact:

Midtronics Inc.

7000 Monroe St.

Willowbrook, IL 60521

Tel: (630) 321-8032

Fax: (630) 323-2844

[www.midtronics.com](http://www.midtronics.com)



## HASTINGS FIBER GLASS PRODUCTS

### Don't drop that fuse-barrel again!

With the 'new' Hastings Fuse-Claw linemen can install and remove cut-out fuses from the ground quickly, safely, and efficiently! The Hastings Fuse-Claw attaches to any telescopic hot stick. Spring tension buttons grip the fuse barrel inside the Claw cradle. Once the fuse barrel is landed in the cut-out a simple wrist-motion will release the spring tension buttons and allow the lineman to proceed with his switching operation.

For more information contact:

Hastings Fiber Glass Products

Tel: (616) 945-9541

Fax: (616) 945-4623

[www.hfpg.com](http://www.hfpg.com)



## WAUKESHA ENGINE, DRESSER INC.

### New Lease Program for Waukesha Engines

Waukesha Engine has announced the details of a new lease program for its popular Enginator( engine/generator packages. According to company officials, the Waukesha Engine Lease Program offers customers the same advantages as owning a distributed power generation system ñ but without the risks.

Waukesha Enginator( engine/generators use clean burning natural gas fuel and are easily permitted in nearly all parts of the United States and Canada, and do not require on-site fuel storage. Pre-packaged with a generator and available in sizes up to 2.9 megawatts each, they are backed by 95 years if experience in the design and manufacture of reciprocating engines.

For more information visit

[www.waukeshaengine.dresser.com](http://www.waukeshaengine.dresser.com)



# Electricity Today Literature Review

## CUTLER-HAMMER

### Products and Services Catalog

Eaton's Cutler-Hammer Products and Services Catalog 2001 provides product descriptions, detailed specification and pricing. You can also learn about the broad spectrum of solutions offered from Cutler-Hammer Engineering Services and Systems (C-H ESS). These catalogs are easy to use and are the most complete industrial resources currently available. Call 1-800-957-7050 to order yours today!



## HUBBELL POWER SYSTEMS

### Polymer Insulated Hookstick Switches

Now with a choice of ESP™ Rubber or porcelain insulators, M3 switches from Hubbell Power Systems are included in a recently updated catalog section of hookstick switches for crossarms, substations and in-line applications on 15 to 35kV systems. Also among the RUS accepted single-phase distribution switches is the ALTD in-line switch with polymer insulator and combined mechanical-electrical connections on the same end fittings.

Please email literature requests to: INFOHPS@HubbellOnline.com



## KABAR INDUSTRIES

### Terminator Secondary Feed-Through

Kabar Industries introduces the Terminator. Using E Block connections allows for easy installation of multiple connections in a safe above ground environment. The Terminator is much easier to change out than a transformer.

Kabar Industries 905-478-8983  
Email: [kabar@kabar-almat.com](mailto:kabar@kabar-almat.com)



## MPHUSKY

### Cabl-Bus


MPHusky's new brochure details the advantages of Cabl-Bus™ Systems to distribute power. These systems offer a reliable alternative for distributing power up to 8,000 amps. Continuous, fully insulated conductors in free air allow for optimum intraphase current balance. Contact MPHusky at 864-234-4800 for a free brochure.



## CANADIAN ELECTRICITY FORUM

### The Canadian Guide to Electrical Maintenance and Equipment Repair Vol. 3

This 96 page reference book contains papers and articles by some of North America's leading experts in electrical maintenance. This guide will update you on some of the most recent techniques and technologies to help keep your electrical distribution system up and running. For only \$25, this is an inexpensive, but very valuable addition to your bookshelf! To order, call us at (905) 509-4448.



## POWER MEASUREMENT LTD.

### Low-cost, compact power & energy meters

The 6200 ION is an affordable, high quality panel meter. Less than 2" deep, it fits ANSI and DIN cutouts. The unit offers a wide range of revenue accurate 3-phase power, energy, demand and harmonics measurements, plus optional Modbus and pulse outputs. Unique plug-in Feature Packs™ let you add additional feature like analog I/O, logging and more, right in the field!

For more information call toll free 877-METER-IT (1-877-638-3748)



# SHOWCASE FOCUS

## WELCOME TO ELECTRICITY TODAY'S SHOWCASE FOCUS



### ENERFIN INC. Duplex Hydrogen Cooler

Enerfin Inc. specializes in the design and manufacture of heat transfer products for the Power Industry. With a complete line of "hydrogen coolers", "transformer oil coolers", "oil pumps", "L.O. coolers", "steam gland condensers", "hydro generator air coolers", and "steam/air heaters", we can cover all of your plant's heat exchanger requirements. Call on our engineers to assist you on your next application.

For more information contact:  
Enerfin Inc.  
Toll Free: 1-800-724-2919  
Fax: (450) 444-4644  
Email: sales@enerfin-inc.com  
www.enerfin-inc.com



### KATO ENGINEERING INC. Generators, Motor-Generator Sets, Controls

Kato Engineering designs and manufactures precision-engineered, top-quality AC generators, motor-generator sets and controls for prime, standby, and peak-shaving power. Kato supplies to the oil & gas, mining, industrial, military, transportation, co-generation, computer and telecommunications markets.

For more information contact:  
Kato Engineering Inc.  
P.O. Box 8447  
Mankato, MN 56002 USA  
Tel: 507-625-4011  
Fax: 507-345-2798  
www.kato-eng.com  
E-mail: katoengineering@lsusa.com  
See us at Power-Gen, Dec. 11-13,  
Las Vegas Convention Center, Booth  
7141



### KLOHN CRIPPEN Power of Experience

Klohn Crippen is one of Canada's premier hydroelectric engineering companies with over 45 years of experience including surface and underground powerhouses, pump storage facilities, tunnels and major earth and rock dam

- Asset evaluation & due diligence
- Permitting & licensing
- Environmental impact
- Dam safety & plant rehabilitation
- Engineering & project management
- Financial structuring

For more information contact:  
Klohn Crippen Consultants  
750 Cambie Street, Suite 600  
Vancouver, BC V6B 2P2  
Tel: 604-669-3800  
Fax: 604-669-3835  
e-mail: gakins@klohn.com  
www.klohn.com



### ALLEN-SHERMAN-HOFF CANADA ASHHandler™ Valve for Vacuum Conveying Systems

The ASHandler™ Valve feeds material from a hopper outlet of electrostatic precipitators, baghouses, and other dry ash collecting systems to the conveying lines. It is available in different sizes and is constructed for easy routine maintenance.

For more information, contact:  
Allen-Sherman-Hoff Canada,  
a division of Diamond Power  
International, Inc.  
6 Jaffray St.  
Cambridge, Ontario N1R 7G8  
1-519-621-1975 in Canada  
1-888-ASH Parts in USA  
1-610-647-9900 internationally  
www.a-s-h.com



### OPTIMUM ENERGY PRODUCTS Model 3731

#### Clamp-On Resistance Tester

Direct reading of ground resistance from 0.01Ω to 1200Ω without the use of auxiliary ground rods. A higher immunity to electrical noise allows for work around transmission towers and substations. The 1.25" (32mm) opening accommodates ground rods, and larger ground conductors up to 1000MCM. The tester is used in multi-grounded systems without disconnecting the ground under test. The Model 3731 is equipped with an alarm function and memory logging function.

www.ElectricityMetering.com  
Optimum Energy Products Ltd.  
Toll Free (877) 766-5412  
Fax: (403) 256-3431  
Email: info@electricitymetering.com

## SHOWCASE FOCUS


**ALSTOM ENERGY  
MANAGEMENT & MARKETS  
e-terradealmaker**

The technology market leader in electricity deregulation, ALSTOM Energy Management & Markets (EMM), offers its exclusive line of software for market management, e-terradealmaker®.

ALSTOM EMM's e-terra® suite of solutions is designed to support limitless transaction growth. E-terradealmaker manages critical trading activities quickly and easily featuring portfolio tracking, accounting and invoicing, risk management, scheduling, marketing and price analysis.

For more information contact:

ALSTOM EMM

Tel: (425) 822-6800

www.esca.com


**KYORITSU**
**Kew High Voltage Insulation Tester**

- high voltage insulation testing up to 100 GΩ at 1kV-10kV output voltage is indicated on a digital display
- easy to read colour coded resistance ranges
- suited for heavy duty electrical maintenance and servicing
- operated by rechargeable HiCad batteries (charger provided)

For more information contact:

RHC & Associates

Tel: (905) 828-6221

Fax: (905) 828-6408

Email: info@rhctest.com

www.rhctest.com


**MARIAH ENERGY CORP.  
Clean Energy Solutions**

As a Distributed Micro Utility Mariah Energy offers:

Purchase or Build-Own-Operate with no capital cost on our Heat PlusPower™ systems.

Pay only for energy used.

- Multi-residential
- Institutional
- Pools
- Industrial
- Hotels

For more information contact:

Mariah Energy Corp.

Tel: (403) 264-2880

Email: info@mariahpower.com

www.mariahpower.com

**Continued from page 5**

had one false operation when it tripped both lines. The cause was traced to the delta voltages that were used to direction the relay. The directioning voltages were replaced by four wire star connected potentials to solve the problem.

The KCEG is a reliable, effective protective device, but it does not initiate tripping until about 60 milliseconds or almost 4 cycles after the fault occurs. It was considered advisable to try to reduce this time and thus the plant's exposure to the inevitable voltage sag, and to replace the ineffective remote tripping function that had previously been removed.

Accordingly, the author developed a prototype relay called the PCS, which incorporates a number of enhanced features to improve performance and reduce cost, as follows:

- The relay operates in 20 ms, about twice as fast as normal remote tripping and three times as fast as the KCEG.
- The relay sends a trip signal directly to the breaker, eliminating the cost and time delay inherent in auxiliary relays.
- A single relay provides protection for

both 115KV lines with separate trip outputs for each transformer breaker.

- The relay is designed to ensure correct directioning for both trip outputs under all voltage collapse conditions.
- The relay is currently configured to trip only when there is reverse current in all three phases. It thus serves the specific purpose of identifying load backfeed conditions, as its function is to replace remote tripping. It should be noted that the relay can also be configured to operate on a single phase of reverse current.
- The pick up setting for the PCS is 500 amps per phase.

The new directional over current protection has been in service for over five years and during that time, except as noted above, the plant has never suffered a single shut down for normal one line faults, nor has the prototype PCS relay either false tripped or failed to trip for the conditions for which it was designed.

The KCEG relays clear slightly more faults than the custom relay, as would be expected because it is designed to operate for all line faults. See fault recorder records of fault cleared by the PCS relay. The fault was a lightning arrester failure

right in the switch yard. The voltage dip lasted only 70 milliseconds.

This pilot project has proven conclusively that instantaneous directional over current relays can replace pilot wire relays and/or remote (transfer) tripping with their associated leased telephone circuits in a dual supply line configuration, at lower cost and with increased reliability. This relay configuration can also be used to connect two feeders from different sources to a common load bus for improved security, provided the two sources can be synchronized.

For comments or more information, Paul Kruger can be reached at (613) 389-3716 or at wkruger1@cogeco.ca. **ET**

**WANTED**

**Power • UPS • NETA Certified  
Field Service Engs • Techs • Mgrs  
Sales • Design • Vibration, Motor Repair,  
Pred/Prev Maintenance**

For 21 years we've specialized in placing people who test, repair, maintain or sell electrical apparatus, electronic or electric power equipment. Nationwide. All fees company paid. Call or send confidential resume to

LISA LINEAL:

**LINEAL** Recruiting Services

46 Copper Kettle Road, Trumbull, CT 06611  
TOLL FREE 877-386-1091 • Fax: 203-386-9788  
Email: lisalinear@lineal.com • www.lineal.com



## ADVERTISERS INDEX

ADVERTISER	PAGE	URL/EMAIL	ELECTRICITYFORUM WEB PAGE
Academy of Infrared Thermography	25	<a href="http://www.infraredtraining.net">www.infraredtraining.net</a>	<a href="http://www.electricityforum.com/products/academy.htm">www.electricityforum.com/products/academy.htm</a>
Allen-Sherman-Hoff Canada	20,28	<a href="http://www.a-s-h.com">www.a-s-h.com</a>	—
ALSTOM EM&M	29,31	<a href="http://www.esca.com">www.esca.com</a>	<a href="http://www.electricityforum.com/products/alstomesca.htm">www.electricityforum.com/products/alstomesca.htm</a>
Amps Abundant	15,25	<a href="http://www.ampsabundant.com">www.ampsabundant.com</a>	—
Beckwith Electric Co. Inc.	8	<a href="http://www.beckwithelectric.com">www.beckwithelectric.com</a>	<a href="http://www.electricityforum.com/products/beck.htm">www.electricityforum.com/products/beck.htm</a>
Cable Master Inc.	23	<a href="http://www.cablemasterinc.com">www.cablemasterinc.com</a>	<a href="http://www.electricityforum.com/products/cablemas.htm">www.electricityforum.com/products/cablemas.htm</a>
Cadtek Inc.	26	<a href="http://www.cadtek.com">www.cadtek.com</a>	<a href="http://www.electricityforum.com/products/cadtek.htm">www.electricityforum.com/products/cadtek.htm</a>
Canadian Electricity Forum	26,27	<a href="http://www.electricityforum.com">www.electricityforum.com</a>	<a href="http://www.electricityforum.com">www.electricityforum.com</a>
Citel Inc.	24	<a href="http://www.citelprotection.com">www.citelprotection.com</a>	<a href="http://www.electricityforum.com/products/cit.htm">www.electricityforum.com/products/cit.htm</a>
The Conklin Sherman Co.	23	<a href="http://www.conklin-sherman.com">www.conklin-sherman.com</a>	<a href="http://www.electricityforum.com/products/conklin.htm">www.electricityforum.com/products/conklin.htm</a>
Cutler-Hammer	10,24,32,27	<a href="http://www.cutler-hammer.com/ess">www.cutler-hammer.com/ess</a>	<a href="http://www.electricityforum.com/products/cutler.htm">www.electricityforum.com/products/cutler.htm</a>
Datel Inc.	7	<a href="http://www.datel.com">www.datel.com</a>	<a href="http://www.electricityforum.com/products/datel.htm">www.electricityforum.com/products/datel.htm</a>
Donaldson Company Inc.	10	<a href="http://www.donaldson.com">www.donaldson.com</a>	—
Electroindustries/Gaugetech	26	<a href="http://www.electroind.com">www.electroind.com</a>	<a href="http://www.electricityforum.com/products/electroi.htm">www.electricityforum.com/products/electroi.htm</a>
Enerfin Inc.	28	<a href="http://www.enerfin-inc.com">www.enerfin-inc.com</a>	—
Flex-Core	25	<a href="http://www.flex-core.com">www.flex-core.com</a>	<a href="http://www.electricityforum.com/products/flex.htm">www.electricityforum.com/products/flex.htm</a>
FLIR Systems Ltd.	18	<a href="http://www.flir.com">www.flir.com</a>	—
GT Wood Company Ltd.	25	<a href="http://www.gtwood.com">www.gtwood.com</a>	<a href="http://www.electricityforum.com/products/gtwood.htm">www.electricityforum.com/products/gtwood.htm</a>
Hastings Fiber Glass Products	26	<a href="http://www.hastings.com">www.hastings.com</a>	<a href="http://www.electricityforum.com/products/hastings.htm">www.electricityforum.com/products/hastings.htm</a>
Hubbell Power Systems	2,11,24,27	<a href="mailto:infoHPS@Hubbellonline.com">infoHPS@Hubbellonline.com</a>	<a href="http://www.electricityforum.com/products/hubbell.htm">www.electricityforum.com/products/hubbell.htm</a>
Intl. Infrared Camera Sales & Leasing	24	<a href="http://www.infraredsales.com">www.infraredsales.com</a>	<a href="http://www.electricityforum.com/products/academy.htm">www.electricityforum.com/products/academy.htm</a>
Kabar Industries	25,27	<a href="http://www.kabar-almat.com">www.kabar-almat.com</a>	<a href="http://www.electricityforum.com/products/kabar.htm">www.electricityforum.com/products/kabar.htm</a>
Kato Engineering Inc.	28	<a href="http://www.kato-eng.com">www.kato-eng.com</a>	—
Kinetrics	17	<a href="http://www.kinetrics.com">www.kinetrics.com</a>	—
Klohn Crippen	28	<a href="http://www.klohn.com">www.klohn.com</a>	—
Rhc & Associates	29	<a href="http://www.rhctest.com">www.rhctest.com</a>	—
Lizco Sales	24	<a href="http://www.lizcosales.com">www.lizcosales.com</a>	<a href="http://www.electricityforum.com/products/lizco.htm">www.electricityforum.com/products/lizco.htm</a>
Mariah Energy Corp.	29	<a href="http://www.mariahpower.com">www.mariahpower.com</a>	—
Midtronics Inc.	26	<a href="http://www.midtronics.com">www.midtronics.com</a>	<a href="http://www.electricityforum.com/products/midtronics.htm">www.electricityforum.com/products/midtronics.htm</a>
MPHusky	27	<a href="http://www.mphusky.com">www.mphusky.com</a>	<a href="http://www.electricityforum.com/products/mphusky.com">www.electricityforum.com/products/mphusky.com</a>
Nynas Canada Inc.	13,23	<a href="http://www.nynas.com">www.nynas.com</a>	—
Onsite Electrical Training inc.	25	<a href="http://http://maxpages.com/onsitetraining.com">http://maxpages.com/onsitetraining.com</a>	<a href="http://www.electricityforum.com/products/onsite.htm">www.electricityforum.com/products/onsite.htm</a>
Optimum Energy Products	28	<a href="http://www.ElectricityMetering.com">www.ElectricityMetering.com</a>	<a href="http://www.electricityforum.com/products/opl.htm">www.electricityforum.com/products/opl.htm</a>
Positron	19,23	<a href="http://www.positronpower.com">www.positronpower.com</a>	<a href="http://www.electricityforum.com/products/positron.htm">www.electricityforum.com/products/positron.htm</a>
Power Measurement Ltd.	27	<a href="http://www.pml.com">www.pml.com</a>	<a href="http://www.electricityforum.com/products/pml.htm">www.electricityforum.com/products/pml.htm</a>
Powertech Labs Inc.	16,24	<a href="http://www.powertechlabs.com">www.powertechlabs.com</a>	<a href="http://www.electricityforum.com/products/powtech.htm">www.electricityforum.com/products/powtech.htm</a>
QMI	21	<a href="http://www.qmi.com">www.qmi.com</a>	—
Radiodetection Canada	22	<a href="http://www.radiodetection.co.uk">www.radiodetection.co.uk</a>	<a href="http://www.electricityforum.com/products/radio.htm">www.electricityforum.com/products/radio.htm</a>
Response Power Inc.	14	<a href="http://www.responsepower.com">www.responsepower.com</a>	—
R.L. Brews Ltd.	4	<a href="http://www.rlbrews.com">www.rlbrews.com</a>	<a href="http://www.electricityforum.com/products/rlbrews.htm">www.electricityforum.com/products/rlbrews.htm</a>
Waukesha Engine Dresser Inc.	26	<a href="http://www.waukeshaengine.dresser.com">www.waukeshaengine.dresser.com</a>	<a href="http://www.electricityforum.com/products/waukesha.htm">www.electricityforum.com/products/waukesha.htm</a>
Wintek Engineering	23	<a href="http://www.wintek-eng.com">www.wintek-eng.com</a>	—
Wire Services	25	<a href="http://www.wireservices.ca">www.wireservices.ca</a>	—
Zensol Automation Inc.	6	<a href="http://www.zensol.com">www.zensol.com</a>	<a href="http://www.electricityforum.com/products/zensol.htm">www.electricityforum.com/products/zensol.htm</a>

**VISIT [www.electricityforum.com/et/online.htm](http://www.electricityforum.com/et/online.htm)**



**e-terra market**

**e-terra grid**

**e-terra trade**

**e-terra supply**

**e-terra retail**

**e-terra disco**

**e-terra service**

**e-terra**  
global energy solutions

**E-terra™ global energy solutions.  
Illuminating possibilities, exceeding expectations.**

The waves of regulatory change within the electricity industry steadily generate major transformations in the structure of utilities around the world. ALSTOM Energy Management and Markets' (EMM's) **e-terra™ global energy solutions** consist of a full line of field-tested products and services for competitive electric utility markets. As with **e-terraoasis™** – the first electric utility business-to-business application for processing transactions over the Internet – ALSTOM EMM continues to light the way for further innovations.

With market-defining energy technology projects around the globe, ALSTOM EMM has the experience, domain expertise and dedicated resources to illuminate the possibilities and exceed expectations of an ever-evolving industry.

For more information visit ALSTOM EMM's Web site at <http://www.tde.alstom.com>.


©ALSTOM - 2001, ALSTOM, the logo ALSTOM and any alternative versions thereof are trademarks and service marks of ALSTOM.  
The e-terra family of products and services are trademarks and/or service marks of ALSTOM ESCA Corporation.

**ALSTOM**

ALSTOM Energy Management & Markets  
11120 NE 33rd Pl  
Bellevue, Washington 98004  
Tel: 425-822-6800  
Fax: 425-889-1700  
[www.tde.alstom.com](http://www.tde.alstom.com)



# What is your Power Strategy?



**What do you want it to be?  
Not sure?**



Regardless of your industry, your Power System is the lifeblood of your business. Without safe and consistent power delivery you're putting employees, production, and profit at risk.

A strong power strategy can enhance equipment performance, reduce operating costs and maximize the reliability, safety and integrity of your electrical equipment and systems. Eaton's Cutler-Hammer Engineering Services and Systems (C-H ESS) is a single-point resource focused on integrating and maintaining power quality.



Industry leaders regard C-H ESS as a dedicated service partner who understands on-site and remote access diagnostics, installation, modernization, preventive maintenance, and turnkey project management. The C-H ESS team is made up of performance-driven engineers and technicians, available 24 hours a day, 7 days a week, providing an unrivaled array of services and solutions.

Don't be left in the dark when it comes to Power Strategies. Call Cutler-Hammer Engineering Services and Systems, 905-631-4246 or 1-800-498-2678, or visit our website at [www.cutlerhammer.eaton.com](http://www.cutlerhammer.eaton.com)



**Cutler-Hammer**

**EATON**